

## ADP-400



### General Features

- ›Support Sprocket and Roll
- ›3ply printing
- ›Cost effective

### Applications

Credit / Debit cards, POS system, Banking system, ECR, Kitchen

### Technical Specifications

Item	Specification			
Printing Method	9-pin serial impact dot matrix			
Print Direction	Bi-directional (with logical seeking)			
No. Of Columns	EPSON TM-U200 EMULATION : 42/35, 40/33      40/33      28/23      40/33 Other EMULATION : 40, 33			
No. Of Total Dots	400 Dots/Line	320 Dots/Line	360 Dots/Line	
Resolutions	160DPI	128 DPI	160 DPI	
Font Size	7 X 9, 9 X 9	5 X 9, 7 X 9	7 X 9, 9 X 9	
Line Spacing	n/144 inch			
Printing Width	63.5mm (2.5 inch)		57.2 mm (2.25inch)	
Print Speed	3 LINE/SEC	3.3 Line/sec	3.5 Line/sec	3.2 Line/sec
Ink Ribbon	EPSON ERC-23 Black, Purple			
Paper	Media	Roll Paper	Fan Fold Paper	

	Width	76.2mm (3 inch)	89mm (3.5 inch)	89mm(3.5inch)	76.2mm(3inch)	76.2mm(3inch)
	Diameter	76.2 mm (3 inch)				
	Copies	Original + 3 copy				
Data Buffer		16K byte				
Cash Drawer Driver		2 circuits(24V, 1A max)				
Interface		RS-232C Serial or Centronics Parallel				
Emulation		EPSON TM-U200, TM-U300, CITIZEN iDP-3540, STAR SP200				
	Type	External adapter				
Power Supply	Input	110/220 VAC, 60 Hz				
	Output	25 VDC 1.5 A				
Operating Condition		5°c to 40°c, 10% to 80% RH				
Storage Condition		-20°c to 60°c, 5% to 95% RH				
Reliability	MCBF	5 million lines				
	Print Head	150 million charaters				
Dimension (WXDXH) (mm)	Non-Cutter	162 X 282 X 138				
	Cutter					
Weight (kg)	Non-Cutter	1.26Kg				
	Cutter					
Certifications		FCC, RRL, UL/cUL, CE-LVD, CE-EMCD				